RESOLUTION NUMBER 1009

A RESOLUTION APPROVING THE ENTRY OF A PURCHASE CONTRACT IN EXCESS OF \$100,000 [PURCHASE OF ONE (1) 2026 MV607 FLATBED DUMP TRUCK FOR THE PUBLIC WORKS DEPARTMENT]

WHEREAS, the City Council (the "Council") of the City of Sumter, South Carolina (the "City"), has enacted an Ordinance entitled "An Ordinance Establishing Procurement Procedures for the City of Sumter, South Carolina" (the "Purchasing Ordinance");

WHEREAS, pursuant to the Purchasing Ordinance, the Council must approve by resolution any purchase contract subject to the Purchasing Ordinance that exceeds \$100,000.00; and

WHEREAS, the Council has been presented with a request to approve a purchase contract (the "Contract") in excess of \$100,000.00;

NOW, THEREFORE, be it resolved as follows:

Section 1. The Council hereby approves the Contract for the supplies, services, equipment, or construction identified below:

SUBJECT: Purchase of One (1) 2026 MV607 Flatbed Dump Truck for the

Public Works Department

CONTRACTOR/VENDOR Carolina International Trucks

Columbia, South Carolina

(via South Carolina State Contract Number 4400037441)

PRICE: \$127,873.68

(Funding Source: Fiscal Year 2025-2026 Budget)

METHOD: Exempted Items (Purchasing Ordinance, Sections II.J.4 and

II.J.5); Supporting materials are attached.

<u>Section 2</u>. The City Manager is hereby authorized to negotiate, execute, and deliver the Contract on behalf of the City in such form and with such additions, deletions, or modifications as he deems necessary or prudent.

ADOPTED THIS 7^{TH} DAY OF OCTOBER 2025, BY SUMTER CITY COUNCIL.

CITY OF SUMTER, SOUTH CAROLINA

David P. Merchant, Mayor			
James B. Blassingame, Mayor Pro Tempore	Calvin K. Hastie, Sr., Councilman		
Colin C. Davis, Councilman	Gifford M. Shaw, Councilman		
Anthony Gibson, Councilman	Rebecca Lynn Kennedy, Councilwoman		
ATTEST:			
Linda D. Hammett. City Clerk			



City of Sumter 21 N. Main Street P.O. Box 1449 Sumter, SC 29150

MEMORANDUM

TO: Deron McCormick, City Manager

FROM: Rich Pring, Director of Public Works

DATE: September 17, 2025

SUBJECT: Request to Purchase One 2026 MV607 Flatbed Dump Truck for Public Works Department

It is the recommendation of Public Services to purchase one new 2026 MV607 Dump Truck from Carolina International Trucks in Columbia South Carolina at the price of \$127,873.68. This quote represents the SC State Contract #44 37441 pricing.

The budgeted amount for one new Flatbed Dump Truck is \$174,000.00.

Attachments: Quote from Carolina International Trucks Photo of like truck

cc: Michael Geddings, Director of Public Services



Prepared For: Sumter, City of Lee Marshall 303 E Liberty St.

Sumter, SC 29150-5040

(803)436 - 2672

Reference ID: 4400037441

Presented By:
CAROLINA INTL TRUCKS
Steve Wiser
PO BOX 7548
COLUMBIA SC 292027548
803-799-4923

Thank you for the opportunity to provide you with the following quotation on a new International truck. I am sure the following detailed specification will meet your operational requirements, and I look forward to serving your business needs.

Model Profile 2026 MV607 SBA (MV607)

AXLE CONFIG: 4X2

APPLICATION: Construction Dump

MISSION: Requested GVWR: 25500. Calc. GVWR: 25500. Calc. GCWR: 33000

Calc. Start / Grade Ability: 29.73% / 2.45% @ 55 MPH

Calc. Geared Speed: 87.3 MPH

DIMENSION: Wheelbase: 211.00, CA: 143.90, Axle to Frame: 75.00

ENGINE, DIESEL: {Cummins B6.7 250} EPA 2024, 250HP @ 2400 RPM, 660 lb-ft Torque @ 1600 RPM, 2600 RPM

Governed Speed, 250 Peak HP (Max)

TRANSMISSION, AUTOMATIC: {Allison 2500 RDS} 6th Generation Controls, Wide Ratio, 6-Speed with Double Overdrive, with

PTO Provision, Less Retarder, with 33,000-lb GVW and GCW Max

CLUTCH: Omit Item (Clutch & Control)

AXLE, FRONT NON-DRIVING: {Dana Spicer D-800F} I-Beam Type, 8,000-lb Capacity

AXLE, REAR, SINGLE: {Meritor MS-17-14X-3DCL} Single Reduction, 17,500-lb Capacity, Driver Controlled Locking

Differential, 190 Wheel Ends Gear Ratio: 5.57

CAB: Conventional, Day Cab

TIRE, FRONT: (2) 11R22.5 Load Range H AH37 (HANKOOK), 499 rev/mile, 75 MPH, All-Position TIRE, REAR: (4) 11R22.5 Load Range G AH37 (HANKOOK), 501 rev/mile, 75 MPH, All-Position

SUSPENSION, REAR, SINGLE: 23,500-lb Capacity, Vari-Rate Springs, with 4500-lb Capacity Auxiliary Rubber Springs

PAINT: Cab schematic 100WP

Location 1: 9219, Winter White (Std)

1

Chassis schematic N/A

4SPA

Vehicle Specifications 2026 MV607 SBA (MV607)

August 27, 2025

Code Description MV60700 Base Chassis, Model MV607 SBA with 211.00 Wheelbase, 143.90 CA, and 75.00 Axle to Frame. 1570 TOW HOOK, FRONT (2) Frame Mounted 1ANA **AXLE CONFIGURATION 4x2** <u>Notes</u> : Pricing may change if axle configuration is changed. FRAME RAILS Heat Treated Alloy Steel (120,000 PSI Yield); 10.375" x 0.438" (263.5mm x 94.1mm 1CAH x 11.1mm); 456.0" (11582mm) Maximum OAL 1LEG LICENSE PLATE HOLDER Includes Upper & Lower Mounting Plate Hardware, Mounted in Existing Holes in Front Bumper 1LNG BUMPER, FRONT Contoured, Steel, Painted Gloss Black WHEELBASE RANGE 199" (505cm) Through and Including 254" (645cm) 1WEJ AXLE, FRONT NON-DRIVING (Dana Spicer D-800F) I-Beam Type, 8,000-lb Capacity 2AEM SUSPENSION, FRONT, SPRING Parabolic Taper Leaf, Shackle Type, 8,000-lb Capacity, with Shock 3ADA Absorbers <u>Includes</u> : SPRING PINS Rubber Bushings, Maintenance-Free : In combinations where chassis component weights may cause a chassis lean, a spring is used in front left spring pack to offset this imbalance & provide a level chassis, within 3/8", with body installed. 4091 BRAKE SYSTEM, AIR Dual System for Straight Truck Applications **Includes** : BRAKE LINES Color and Size Coded Nylon : DRAIN VALVE Twist-Type : GAUGE, AIR PRESSURE (2) Air 1 and Air 2 Gauges; Located in Instrument Cluster : PARKING BRAKE CONTROL Yellow Knob, Located on Instrument Panel : PARKING BRAKE VALVE For Truck : QUICK RELEASE VALVE On Rear Axle for Spring Brake Release: 1 for 4x2, 2 for 6x4 : SPRING BRAKE MODULATOR VALVE R-7 for 4x2, SR-7 with relay valve for 6x4/8x6 TRAILER CONNECTIONS Four-Wheel, with Hand Control Valve and Tractor Protection Valve, for Straight 4619 Truck Notes : When electronic stability control is ordered with trailer connections on a 4x2 truck, please check the operator manual for trailer weight restrictions. 4AZA AIR BRAKE ABS {Bendix AntiLock Brake System} 4-Channel (4 Sensor/4 Modulator) Full Vehicle Wheel Control System AIR DRYER (Bendix AD-9SI) with Heater, Includes Safety Valve 4EDN 4EXP BRAKE CHAMBERS, FRONT AXLE (Bendix) 20 Sqln BRAKE CHAMBERS, REAR AXLE {Bendix EverSure} 30/30 Sqln Spring Brake 4EXU 4GBM BRAKE, PARKING Manual Push-Pull Pneumatic Parking Brake SLACK ADJUSTERS, FRONT (Haldex) Automatic 4LAA SLACK ADJUSTERS, REAR {Haldex} Automatic 4LGA

2

AIR COMPRESSOR (Cummins) 18.7 CFM

Proposal: 25124-01

Vehicle Specifications 2026 MV607 SBA (MV607)

August 27, 2025

<u>Code</u> <u>Description</u>

4VLE AIR DRYER LOCATION Mounted Inside Engine Compartment, Right Side

4WDM DUST SHIELDS, REAR BRAKE for Air Cam Brakes

4XDC BRAKES, FRONT {Meritor 15X4 Q-PLUS CAST} Air S-Cam Type, Cast Spider, Fabricated Shoe, Double

Anchor Pin, Size 15" X 4", 13,200-lb Capacity

4XDR BRAKES, REAR {Meritor 16.5X7 Q-PLUS CAST} Air S-Cam Type, Cast Spider, Fabricated Shoe, Double

Anchor Pin, Size 16.5" X 7", 23,000-lb Capacity per Axle

4XEZ AIR TANK LOCATION (2) Mounted Between the Rails, Back of Cab, One on Each Side, Parallel to Rails

5708 STEERING COLUMN Tilting

5CAW STEERING WHEEL 4-Spoke; 18" Dia., Black

5PRG STEERING GEAR (TRW TAS40) Power

6DGG DRIVELINE SYSTEM {Dana Spicer} 1710, for 4x2/6x2

7BEV AFTERTREATMENT COVER Steel, Black

7BLW EXHAUST SYSTEM Horizontal Aftertreatment System, Frame Mounted Right Side Under Cab, for Single

Vertical Tail Pipe, Frame Mounted Right Side Back of Cab

7WAZ TAIL PIPE (1) Turnback Type

7WDM EXHAUST HEIGHT 10'

7WDN MUFFLER/TAIL PIPE GUARD (1) Aluminum

8000 ELECTRICAL SYSTEM 12-Volt, Standard Equipment

Includes

: DATA LINK CONNECTOR For Vehicle Programming and Diagnostics In Cab

: HAZARD SWITCH Push On/Push Off, Located on Instrument Panel to Right of Steering Wheel

: HEADLIGHT DIMMER SWITCH Integral with Turn Signal Lever : PARKING LIGHT Integral with Front Turn Signal and Rear Tail Light

: STARTER SWITCH Electric, Key Operated

: STOP, TURN, TAIL & B/U LIGHTS Dual, Rear, Combination with Reflector

: TURN SIGNAL SWITCH Self-Cancelling for Trucks, Manual Cancelling for Tractors, with Lane Change

Feature

: TURN SIGNALS, FRONT Includes Reflectors and Auxiliary Side Turn Signals, Solid State Flashers; Flush

Mounted

: WINDSHIELD WIPER SWITCH 2-Speed with Wash and Intermittent Feature (5 Pre-Set Delays), Integral with

Turn Signal Lever

: WINDSHIELD WIPERS Single Motor, Electric, Cowl Mounted

: WIRING, CHASSIS Color Coded and Continuously Numbered

8518 CIGAR LIGHTER Includes Ash Cup

8GXD ALTERNATOR {Leece-Neville AVI160P2013} Brush Type, 12 Volt, 160 Amp Capacity, Pad Mount, with

Remote Sense

8HAE BODY BUILDER WIRING Rear of Frame; Includes Sealed Connectors for Tail/Amber Turn/Marker/ Backup/

Accessory Power/Ground and Sealed Connector for Stop/Turn

8HAH ELECTRIC TRAILER BRAKE/LIGHTS Accommodation Package to Rear of Frame; for Combined Trailer Stop,

Tail, Turn, Marker Light Circuits; Includes Electric Trailer Brake Accommodation Package with Cab

Connections for Mounting Customer Installed Electric Brake Unit, Less Trailer Socket

8MJT BATTERY SYSTEM {Fleetrite} Maintenance-Free, (2) 12-Volt 1900CCA Total, Top Threaded Stud

8RGA 2-WAY RADIO Wiring Effects; Wiring with 20 Amp Fuse Protection, Includes Ignition Wire with 5 Amp Fuse,

Wire Ends Heat Shrink and Routed to Center of Header Console in Cab

Vehicle Specifications 2026 MV607 SBA (MV607)

August 27, 2025

<u>Code</u> <u>Description</u>

8RMZ SPEAKERS (2) 6.5" Dual Cone Mounted in Both Doors, (2) 5.25" Dual Cone Mounted in Both B-Pillars

8RPP ANTENNA Shark Fin, Roof Mounted

8RPS RADIO AM/FM/WB/Clock/Bluetooth/USB Input/Auxiliary Input

8RRK CAMERA SYSTEM Prewire, Four Camera Input Capable, Camera One Input Pre-configured for Reverse, Blunt

Cut Circuits for Three Camera Inputs, Includes One Camera in Bag Shipped Loose in Cab, Display Mounted

to Dash, 5' Cable Coiled at End of Frame

8TKK TRAILER AUXILIARY FEED CIRCUIT for Electric Trailer Brake Accommodation/Air Trailer ABS; with 30 Amp

Fuse and Relay, Controlled by Ignition Switch

8TPR STOP, TURN, TAIL & B/U LIGHTS {Weldon} Multi-Function LED Lamp, Mounted Outside Rails, Includes LED

License Plate Light

8VBE HORN, ELECTRIC (1) Trumpet Style

8VZK TURN SIGNALS, FRONT Dual Face, LED, Amber/Red, Mounted on Top of Fender, Used with Standard Flush

Mounted Front Turn Signal, Side Marker Lamps, Parking Lights and Reflectors

8WPH CLEARANCE/MARKER LIGHTS (5) {Truck Lite} Amber LED Lights, Flush Mounted on Cab or Sunshade

8WPZ TEST EXTERIOR LIGHTS Pre-Trip Inspection will Cycle all Exterior Lamps Except Back-up Lights
8WTK STARTING MOTOR {Delco Remy 38MT Type 300} 12 Volt, Less Thermal Over-Crank Protection

8WWJ INDICATOR, LOW COOLANT LEVEL with Audible Alarm

8XAH CIRCUIT BREAKERS Manual-Reset (Main Panel) SAE Type III with Trip Indicators, Replaces All Fuses

8XDU BATTERY BOX Steel, with Aluminum Cover, 14" Wide, 2-3 Battery Capacity, Mounted Left Side Under Cab

8XHN HORN, AIR Single Trumpet, Black, with Lanyard Pull Cord

8XNY HEADLIGHTS Halogen

8XPN USB PORT One USB-A Port and One USB-C Port, Located in Instrument Panel

9AAB LOGOS EXTERIOR Model Badges

9AAE LOGOS EXTERIOR, ENGINE Badges

9HCW GRILLE Molded in Black

9WBN FENDER EXTENSIONS Painted

9WBW FRONT END Tilting, Fiberglass, with Three Piece Construction, Dual Air Intakes

10060 PAINT SCHEMATIC, PT-1 Single Color, Design 100

<u>Includes</u>

: PAINT SCHEMATIC ID LETTERS "WP"

10761 PAINT TYPE Base Coat/Clear Coat, 1-2 Tone

10AGB COMMUNICATIONS MODULE Telematics Device with Over the Air Programming; Includes Five Year Data

Plan and International 360

10UAV VEHICLE REGISTRATION IDENTITY ID for Non-CARB Omnibus and/or Non-ACT Adopting State or Exempt

Vehicle. Not for use on vehicles registering in CA/MA /OR/NJ/NY/WA. Contains non-mitigated legacy engine & cannot be registered in CA unless exempt. You may be held liable under state law for failure to properly

register vehicle.

<u>Notes</u>

: CANNOT BE REGISTERED IN CA. For vehicles that will be registered in States other than CA.

10WCY SAFETY TRIANGLES

**		
44	INTERNATIONAL	

<u>Vehicle Specifications</u> 2026 MV607 SBA (MV607)

August 27, 2025

Code	Description
10WUE	MUD FLAPS, FRONT WHEELS (2) Rubber, Mounted on Fender Extension
10XAN	FIRE EXTINGUISHER 5 lb Class A B C
10XAP	FIRE EXTINGUISHER BRACKET Mounted Left Side Driver Seat
11001	CLUTCH Omit Item (Clutch & Control)
12703	ANTI-FREEZE Red, Extended Life Coolant; To -40 Degrees F/ -40 Degrees C, Freeze Protection
12849	BLOCK HEATER, ENGINE 120V/1000W, for Cummins ISB/B6.7/ISL/L9 Engines
	<u>Includes</u> : BLOCK HEATER SOCKET Receptacle Type; Mounted below Drivers Door
12EXU	ENGINE, DIESEL (Cummins B6.7 250) EPA 2024, 250HP @ 2400 RPM, 660 lb-ft Torque @ 1600 RPM, 2600 RPM Governed Speed, 250 Peak HP (Max)
12THT	FAN DRIVE {Horton Drivemaster} Two-Speed Type, Direct Drive, with Residual Torque Device for Disengaged Fan Speed
	Includes : FAN Nylon
12VCE	AIR CLEANER Single Element, Fire Retardant Media
12VKB	EMISSION, CALENDAR YEAR {Cummins B6.7} EPA, OBD and GHG Certified for Calendar Year 2025
12VXV	THROTTLE, HAND CONTROL Engine Speed Control for PTO; Electronic, Mobile, Variable Speed; (Range 2 to 20 MPH) Mounted on Steering Wheel
12WPV	OIL PAN 15 Quart Capacity, For Cummins ISB/B6.7 Engines
12WVG	EPA IDLE COMPLIANCE Low NOx Idle Engine, Complies with EPA Clean Air Regulations; Includes "Certified Clean Idle" Decal on Hood
12WZE	CARB IDLE COMPLIANCE Does Not Comply with California Clean Air Idle Regulations
12XBM	ENGINE CONTROL, REMOTE MOUNTED Provision for; Includes Wiring for Body Builder Installation of PTO Controls and Starter Lockout, with Ignition Switch Control, for Cummins B6.7 and L9 Engines
12XCC	RADIATOR Aluminum, 2-Row, Down Flow, Front to Back System, 640 SqIn Louvered, with 383 SqIn Charge Air Cooler, Includes In-Tank Oil Cooler
12XCS	CARB EMISSION WARR COMPLIANCE Does Not Comply with CARB Emission Warranty
13BBK	TRANSMISSION, AUTOMATIC {Allison 2500 RDS} 6th Generation Controls, Wide Ratio, 6-Speed with Double Overdrive, with PTO Provision, Less Retarder, with 33,000-lb GVW and GCW Max
13WDH	WIRING, TRANSMISSION Installed Wiring for Transmission/PTO Controls, for Allison 1000, 2000, 2100, 2200, 2400, 2500 Series Transmission
13WEX	TRANSMISSION SHIFT CONTROL Column Mounted Stalk Shifter, for Allison 1000 & 2000 Series Transmission
13WLN	TRANSMISSION OIL Synthetic; 20 thru 28 Pints
13WUA	AUTOMATIC NEUTRAL Allison Transmission Shifts to Neutral When Parking Brake is Engaged and Remains in Neutral When Parking Brake is Disengaged, with On/Off Switch
13WVV	NEUTRAL AT STOP Allison Transmission Shifts to Neutral When Service Brake is Depressed and Vehicle is at Stop; Remains in Neutral Until Service Brake is Released
13WYY	SHIFT CONTROL PARAMETERS (Allison) 1000 or 2000 Series Transmissions, Performance Programming
13XAA	PTO CONTROL, DASH MOUNTED For Customer Provided PTO; Includes Switch, Electric/Air Solenoid, Piping and Wiring

5

Proposal: 25124-01

Vehicle Specifications 2026 MV607 SBA (MV607)

August 27, 2025

<u>Code</u> <u>Description</u>

13XAC ALLISON SPARE INPUT/OUTPUT for Rugged Duty Series (RDS), General Purpose Trucks, Package Number

354, Modified for Single Input Auto Neutral

13XAK PTO LOCATION Customer Intends to Install PTO at Right Side of Transmission

14ANR AXLE, REAR, SINGLE {Meritor MS-17-14X-3DCL} Single Reduction, 17,500-lb Capacity, Driver Controlled

Locking Differential, 190 Wheel Ends . Gear Ratio: 5.57

14VAH SUSPENSION, REAR, SINGLE 23,500-lb Capacity, Vari-Rate Springs, with 4500-lb Capacity Auxiliary Rubber

Springs

15LMR FUEL/WATER SEPARATOR {Racor 400 Series,} with Primer Pump, Includes Water-in-Fuel Sensor

15LRE LOCATION FUEL/WATER SEPARATOR Mounted Under Hood, Left Side, Above Front Axle

15SXJ FUEL TANK Top Draw, Non-Polished Aluminum, 24" Dia, 50 US Gal (189L), Mounted Left Side, Under Cab

15WCN DEF TANK 5 US Gal (19L) Capacity, Frame Mounted Outside Left Rail, Under Cab

16030 CAB Conventional, Day Cab

<u>Includes</u>

: CLEARANCE/MARKER LIGHTS (5) Flush Mounted

16BAM AIR CONDITIONER with Integral Heater and Defroster

16GED GAUGE CLUSTER Base Level; English with English Electronic Speedometer

Includes

: GAUGE CLUSTER DISPLAY: Base Level (3" Monochromatic Display), Premium Level (5" LCD Color Display); Odometer, Voltmeter, Diagnostic Messages, Gear Indicator, Trip Odometer, Total Engine Hours, Trip

Hours, MPG, Distance to Empty/Refill for

 $: {\sf GAUGE\ CLUSTER\ Speedometer,\ Tachometer,\ Engine\ Coolant\ Temp,\ Fuel\ Gauge,\ DEF\ Gauge,\ Oil\ Pressure}$

Gauge, Primary and Secondary Air Pressure or Auxiliary Air Pressure (if Air Equipped)

: WARNING SYSTEM Low Fuel, Low DEF, Low Oil Pressure, High Engine Coolant Temp, Low Battery Voltage

(Visual and Audible), Low Air Pressure, Primary and Secondary (if Air Equipped)

16GHU GRAB HANDLE, CAB INTERIOR (2) Safety Yellow

16HGH GAUGE, OIL TEMP, AUTO TRANS for Allison Transmission

16HHE GAUGE, AIR CLEANER RESTRICTION (Filter-Minder) Mounted in Instrument Panel

16HKT IP CLUSTER DISPLAY On Board Diagnostics Display of Fault Codes in Gauge Cluster

16KCA SEAT, DRIVER (National 2000 195) Air Suspension, High Back with Integral Headrest, Vinyl, Isolator, 8"

Adjuster, 1 Chamber Lumbar, 2 Position Front Cushion Adjust, 6-23 Degree Seat Back Angle Adjust, Dual

Shocks

16SMP SEAT, TWO-MAN PASSENGER (National) Vinyl, Less Under Seat Storage Compartment

16SNS MIRRORS (2) Aero Pedestal, Power Adjust, Heated, Black Heads and Arms, 6.5" x 14" Flat Glass, Includes

6

6.5" x 6" Convex Mirrors, for 102" Load Width

<u>Notes</u>

: Mirror Dimensions are Rounded to the Nearest 0.5"

16SNW MIRROR, CONVEX, LOOK DOWN Right Side, Black, 6" x 10.5"

16VKB CAB INTERIOR TRIM Classic, for Day Cab

<u>Includes</u>

: CONSOLE, OVERHEAD Molded Plastic with Dual Storage Pockets, Retainer Nets and CB Radio Pocket;

Located Above Driver and Passenger

: DOME LIGHT, CAB Door Activated and Push On-Off at Light Lens, Timed Theater Dimming, Integral to

Overhead Console, Center Mounted

Proposal: 25124-01

<u>Code</u>	<u>Description</u> : SUN VISOR (2) Padded Vinyl; 2 Moveable (Front-to-Side) Primary Visors, Driver Side with Toll Ticket Strap
16VLK	CAB REAR SUSPENSION Air Suspension, for Mid Cab Height
16WBY	ARM REST, RIGHT, DRIVER SEAT
16WHJ	HOSE CLAMPS, HEATER HOSE {Breeze} Belleville Washer Type
16WJU	WINDOW, POWER (2) and Power Door Locks, Left and Right Doors, Includes Express Down Feature
16WLS	FRESH AIR FILTER Attached to Air Intake Cover on Cowl Tray in Front of Windshield Under Hood
16WSE	LOW WASHER FLUID INDICATOR
16XDS	TELEMATICS BRACKET with Universal Mount, 1" Ball Mount Size, for Customer Supplied Telematics Device, Mounted in Auxiliary Gauge Location in Flat Panel, Includes (1) APO, (1) USB-A Port, (1) USB-C Port
16XJN	INSTRUMENT PANEL Flat Panel
16XWD	SUNSHADE, EXTERIOR Aerodynamic, Painted Roof Color, with Integral Clearance/Marker Lights
16ZBT	ACCESS, CAB Steel, Driver & Passenger Sides, Two Steps per Door, for use with Day Cab and Extended Cab
27DJM	WHEELS, FRONT (Maxion 91541) DISC; 22.5x8.25 Rims, Painted Steel, 2-Hand Hole, 10-Stud, 285.75mm BC, Hub-Piloted, Flanged Nut, with Steel Hubs
28DJM	WHEELS, REAR (Maxion 91541) DUAL DISC; 22.5x8.25 Rims, Painted Steel, 2-Hand Hole, 10-Stud, 285.75mm BC, Hub-Piloted, Flanged Nut, with Steel Hubs
29PAR	PAINT IDENTITY, FRONT WHEELS Disc Front Wheels; with Vendor Applied White Powder Coat Paint
29PAS	PAINT IDENTITY, REAR WHEELS Disc Rear Wheels; with Vendor Applied White Powder Coat Paint
29WLK	WHEEL BEARING, FRONT, LUBE {EmGard FE-75W-90} Synthetic Oil
7372135809	(4) TIRE, REAR 11R22.5 Load Range G AH37 (HANKOOK), 501 rev/mile, 75 MPH, All-Position
7382135809	(2) TIRE, FRONT 11R22.5 Load Range H AH37 (HANKOOK), 499 rev/mile, 75 MPH, All-Position
	Services Section:
40129	WARRANTY Standard for MV Series, Effective with Vehicles Built July 1, 2017 or Later, CTS-2020A
40RBG	SERVICES, TOWING Service Call to 24-Month/Unlimited Mileage to the Nearest Navistar Dealer for Navistar Warrantable Failure as Contract Defined; Includes Engine Failure if Supplier Declines Tow Coverage & ESC Supplied thru Navistar; \$550 (USA) Maximum Benefit per Incident
40TUU	SRV CONTRACT, EXT ALLISON XMSN To 60-Month/Unlimited Miles/km, for Allison 2500 RDS with P&D or Beverage Vocations (ST09-ST13)
40YYK	SRV CONT, EXT CUMMINS ENG/AFTR To 60-Month/150,000 Miles (240,000 km), Extended Cummins B6.7 Engine Coverage, Protection Plan 1 and Aftertreatment, (Truck Application Only)
1	10 ft Godwin dump
	tariff

7

Financial Summary 2026 MV607 SBA (MV607)

(US DOLLAR)

<u>Description</u>	Price
Total Factory List Price Including Options: Total Goods Purchased: Lot charge	\$142,187.00 \$2,000.00
Freight fuel	
Total Preparation And Delivery:	\$1,000.00
Freight	
Total Freight:	\$3,100.00
Total Factory List Price Including Freight:	\$148,287.00
Less Customer Allowance:	(\$51,578.32)
Total Vehicle Price:	\$96,708.68
Total Body/Allied Equipment:	\$30,665.00
Total Sale Price:	\$127,373.68
Total Per Vehicle Sales Price:	\$127,373.68
Total Net Sales Excluding Taxes:	\$127,373.68
IMF	
Total License, Title:	\$500.00
Net Sales Price:	\$127,873.68

Please feel free to contact me regarding these specifications should your interests or needs change. I am confident you will be pleased with the quality and service of an International vehicle.

Approved by Seller:	Accepted by Purchaser:
Official Title and Date	Firm or Business Name
Authorized Signature	Authorized Signature and Date
This proposal is not binding upon the seller without Seller's Authorized Signature	
	Official Title and Date

The TOPS FET calculation is an estimate for reference purposes only. The seller or retailer is responsible for calculating and reporting/paying appropriate FET to the IRS.

The limited warranties applicable to the vehicles described herein are Navistar, Inc.'s standard printed warranties which are incorporated herein by reference and to which you have been provided a copy and hereby agree to their terms and conditions.

