

**RESOLUTION NUMBER 1007**

**A RESOLUTION APPROVING THE ENTRY OF A  
PURCHASE CONTRACT IN EXCESS OF \$100,000  
[PURCHASE OF ONE (1) 2026 MV607 DUMP TRUCK FOR THE WATER AND SEWER DEPARTMENT]**

**WHEREAS**, the City Council (the “Council”) of the City of Sumter, South Carolina (the “City”), has enacted an Ordinance entitled “An Ordinance Establishing Procurement Procedures for the City of Sumter, South Carolina” (the “Purchasing Ordinance”);

**WHEREAS**, pursuant to the Purchasing Ordinance, the Council must approve by resolution any purchase contract subject to the Purchasing Ordinance that exceeds \$100,000.00; and

**WHEREAS**, the Council has been presented with a request to approve a purchase contract (the “Contract”) in excess of \$100,000.00;

**NOW, THEREFORE**, be it resolved as follows:

**Section 1.** The Council hereby approves the Contract for the supplies, services, equipment, or construction identified below:

|                          |                                                                                                                    |
|--------------------------|--------------------------------------------------------------------------------------------------------------------|
| <b>SUBJECT:</b>          | Purchase of One (1) 2026 MV607 Dump Truck for the Water and Sewer Department                                       |
| <b>CONTRACTOR/VENDOR</b> | Carolina International Trucks<br>Columbia, South Carolina<br>(via South Carolina State Contract Number 4400037441) |
| <b>PRICE:</b>            | \$125,320.43<br>(Funding Source: Fiscal Year 2025-2026 Budget)                                                     |
| <b>METHOD:</b>           | Exempted Items (Purchasing Ordinance, Sections II.J.4 and II.J.5); Supporting materials are attached.              |

**Section 2.** The City Manager is hereby authorized to negotiate, execute, and deliver the Contract on behalf of the City in such form and with such additions, deletions, or modifications as he deems necessary or prudent.

**ADOPTED THIS 7<sup>TH</sup> DAY OF OCTOBER 2025, BY SUMTER CITY COUNCIL.**

**CITY OF SUMTER, SOUTH CAROLINA**

\_\_\_\_\_  
David P. Merchant, Mayor

\_\_\_\_\_  
James B. Blassingame, Mayor Pro Tempore

\_\_\_\_\_  
Calvin K. Hastie, Sr., Councilman

\_\_\_\_\_  
Colin C. Davis, Councilman

\_\_\_\_\_  
Gifford M. Shaw, Councilman

\_\_\_\_\_  
Anthony Gibson, Councilman

\_\_\_\_\_  
Rebecca Lynn Kennedy, Councilwoman

**ATTEST:**

\_\_\_\_\_  
Linda D. Hammett, City Clerk



City of Sumter  
21 N. Main Street  
P.O. Box 1449  
Sumter, SC 29150

## MEMORANDUM

TO: Deron McCormick, City Manager

FROM: Rich Pring, Director of Public Works

DATE: September 17, 2025

SUBJECT: Request to Purchase One 2026 MV607 Dump Truck for Water and Sewer Department

---

It is the recommendation of Public Services to purchase one new 2026 MV607 Dump Truck from Carolina International Trucks in Columbia South Carolina at the price of \$125,320.43. This quote represents the SC State Contract #4400037441 pricing.

The budgeted amount for one new Flatbed Dump Truck is \$175,000.00.

Attachments:

Quote from Carolina International Trucks

Photo of like truck

cc: Michael Geddings, Director of Public Services

**Prepared For:**

Sumter, City of  
Lee Marshall  
303 E Liberty St.  
Sumter, SC 29150-5040  
(803)436 - 2672  
Reference ID: 4400037441

**Presented By:**

CAROLINA INTL TRUCKS  
Steve Wiser  
PO BOX 7548  
COLUMBIA SC 292027548  
803-799-4923

Thank you for the opportunity to provide you with the following quotation on a new International truck. I am sure the following detailed specification will meet your operational requirements, and I look forward to serving your business needs.

**Model Profile**  
**2026 MV607 SBA (MV607)**

|                                  |                                                                                                                                                             |
|----------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>AXLE CONFIG:</b>              | 4X2                                                                                                                                                         |
| <b>APPLICATION:</b>              | Construction Dump                                                                                                                                           |
| <b>MISSION:</b>                  | Requested GVWR: 35000. Calc. GVWR: 25500. Calc. GCWR: 33000<br>Calc. Start / Grade Ability: 21.05% / 1.62% @ 55 MPH<br>Calc. Geared Speed: 87.3 MPH         |
| <b>DIMENSION:</b>                | Wheelbase: 152.00, CA: 84.90, Axle to Frame: 75.00                                                                                                          |
| <b>ENGINE, DIESEL:</b>           | {Cummins B6.7 250} EPA 2024, 250HP @ 2400 RPM, 660 lb-ft Torque @ 1600 RPM, 2600 RPM<br>Governed Speed, 250 Peak HP (Max)                                   |
| <b>TRANSMISSION, AUTOMATIC:</b>  | {Allison 2500 RDS} 6th Generation Controls, Wide Ratio, 6-Speed with Double Overdrive, with<br>PTO Provision, Less Retarder, with 33,000-lb GVW and GCW Max |
| <b>CLUTCH:</b>                   | Omit Item (Clutch & Control)                                                                                                                                |
| <b>AXLE, FRONT NON-DRIVING:</b>  | {Dana Spicer D-800F} I-Beam Type, 8,000-lb Capacity                                                                                                         |
| <b>AXLE, REAR, SINGLE:</b>       | {Meritor MS-17-14X-3DCL} Single Reduction, 17,500-lb Capacity, Driver Controlled Locking<br>Differential, 190 Wheel Ends Gear Ratio: 5.57                   |
| <b>CAB:</b>                      | Conventional, Day Cab                                                                                                                                       |
| <b>TIRE, FRONT:</b>              | (2) 11R22.5 Load Range H AH37 (HANKOOK), 499 rev/mile, 75 MPH, All-Position                                                                                 |
| <b>TIRE, REAR:</b>               | (4) 11R22.5 Load Range G AH37 (HANKOOK), 501 rev/mile, 75 MPH, All-Position                                                                                 |
| <b>SUSPENSION, REAR, SINGLE:</b> | 23,500-lb Capacity, Vari-Rate Springs, with 4500-lb Capacity Auxiliary Rubber Springs                                                                       |
| <b>PAINT:</b>                    | Cab schematic 100WP<br>Location 1: 9219, Winter White (Std)<br>Chassis schematic N/A                                                                        |

| <b>Code</b> | <b>Description</b>                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|-------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| MV60700     | Base Chassis, Model MV607 SBA with 152.00 Wheelbase, 84.90 CA, and 75.00 Axle to Frame.                                                                                                                                                                                                                                                                                                                                                                 |
| 1570        | TOW HOOK, FRONT (2) Frame Mounted                                                                                                                                                                                                                                                                                                                                                                                                                       |
| 1ANA        | AXLE CONFIGURATION 4x2                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|             | <u>Notes</u><br>: Pricing may change if axle configuration is changed.                                                                                                                                                                                                                                                                                                                                                                                  |
| 1CAH        | FRAME RAILS Heat Treated Alloy Steel (120,000 PSI Yield); 10.375" x 3.705" x 0.438" (263.5mm x 94.1mm x 11.1mm); 456.0" (11582mm) Maximum OAL                                                                                                                                                                                                                                                                                                           |
| 1LEG        | LICENSE PLATE HOLDER Includes Upper & Lower Mounting Plate Hardware, Mounted in Existing Holes in Front Bumper                                                                                                                                                                                                                                                                                                                                          |
| 1LNG        | BUMPER, FRONT Contoured, Steel, Painted Gloss Black                                                                                                                                                                                                                                                                                                                                                                                                     |
| 1WEH        | WHEELBASE RANGE 134" (340cm) Through and Including 197" (500cm)                                                                                                                                                                                                                                                                                                                                                                                         |
| 2AEM        | AXLE, FRONT NON-DRIVING {Dana Spicer D-800F} I-Beam Type, 8,000-lb Capacity                                                                                                                                                                                                                                                                                                                                                                             |
| 3ADA        | SUSPENSION, FRONT, SPRING Parabolic Taper Leaf, Shackle Type, 8,000-lb Capacity, with Shock Absorbers                                                                                                                                                                                                                                                                                                                                                   |
|             | <u>Includes</u><br>: SPRING PINS Rubber Bushings, Maintenance-Free                                                                                                                                                                                                                                                                                                                                                                                      |
|             | <u>Notes</u><br>: In combinations where chassis component weights may cause a chassis lean, a spring is used in front left spring pack to offset this imbalance & provide a level chassis, within 3/8", with body installed.                                                                                                                                                                                                                            |
| 4091        | BRAKE SYSTEM, AIR Dual System for Straight Truck Applications                                                                                                                                                                                                                                                                                                                                                                                           |
|             | <u>Includes</u><br>: BRAKE LINES Color and Size Coded Nylon<br>: DRAIN VALVE Twist-Type<br>: GAUGE, AIR PRESSURE (2) Air 1 and Air 2 Gauges; Located in Instrument Cluster<br>: PARKING BRAKE CONTROL Yellow Knob, Located on Instrument Panel<br>: PARKING BRAKE VALVE For Truck<br>: QUICK RELEASE VALVE On Rear Axle for Spring Brake Release: 1 for 4x2, 2 for 6x4<br>: SPRING BRAKE MODULATOR VALVE R-7 for 4x2, SR-7 with relay valve for 6x4/8x6 |
| 4619        | TRAILER CONNECTIONS Four-Wheel, with Hand Control Valve and Tractor Protection Valve, for Straight Truck                                                                                                                                                                                                                                                                                                                                                |
|             | <u>Notes</u><br>: When electronic stability control is ordered with trailer connections on a 4x2 truck, please check the operator manual for trailer weight restrictions.                                                                                                                                                                                                                                                                               |
| 4AZA        | AIR BRAKE ABS {Bendix AntiLock Brake System} 4-Channel (4 Sensor/4 Modulator) Full Vehicle Wheel Control System                                                                                                                                                                                                                                                                                                                                         |
| 4EDN        | AIR DRYER {Bendix AD-9SI} with Heater, Includes Safety Valve                                                                                                                                                                                                                                                                                                                                                                                            |
| 4EXP        | BRAKE CHAMBERS, FRONT AXLE {Bendix} 20 SqIn                                                                                                                                                                                                                                                                                                                                                                                                             |
| 4EXU        | BRAKE CHAMBERS, REAR AXLE {Bendix EverSure} 30/30 SqIn Spring Brake                                                                                                                                                                                                                                                                                                                                                                                     |
| 4GBM        | BRAKE, PARKING Manual Push-Pull Pneumatic Parking Brake                                                                                                                                                                                                                                                                                                                                                                                                 |
| 4LAA        | SLACK ADJUSTERS, FRONT {Haldex} Automatic                                                                                                                                                                                                                                                                                                                                                                                                               |
| 4LGA        | SLACK ADJUSTERS, REAR {Haldex} Automatic                                                                                                                                                                                                                                                                                                                                                                                                                |
| 4SPA        | AIR COMPRESSOR {Cummins} 18.7 CFM                                                                                                                                                                                                                                                                                                                                                                                                                       |

| <b><u>Code</u></b> | <b><u>Description</u></b>                                                                                                                                                                                                                                                               |
|--------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 4VLE               | AIR DRYER LOCATION Mounted Inside Engine Compartment, Right Side                                                                                                                                                                                                                        |
| 4WDM               | DUST SHIELDS, REAR BRAKE for Air Cam Brakes                                                                                                                                                                                                                                             |
| 4XDC               | BRAKES, FRONT {Meritor 15X4 Q-PLUS CAST} Air S-Cam Type, Cast Spider, Fabricated Shoe, Double Anchor Pin, Size 15" X 4", 13,200-lb Capacity                                                                                                                                             |
| 4XDR               | BRAKES, REAR {Meritor 16.5X7 Q-PLUS CAST} Air S-Cam Type, Cast Spider, Fabricated Shoe, Double Anchor Pin, Size 16.5" X 7", 23,000-lb Capacity per Axle                                                                                                                                 |
| 4XEZ               | AIR TANK LOCATION (2) Mounted Between the Rails, Back of Cab, One on Each Side, Parallel to Rails                                                                                                                                                                                       |
| 5708               | STEERING COLUMN Tilting                                                                                                                                                                                                                                                                 |
| 5CAW               | STEERING WHEEL 4-Spoke; 18" Dia., Black                                                                                                                                                                                                                                                 |
| 5PRG               | STEERING GEAR {TRW TAS40} Power                                                                                                                                                                                                                                                         |
| 6DGG               | DRIVELINE SYSTEM {Dana Spicer} 1710, for 4x2/6x2                                                                                                                                                                                                                                        |
| 7BEV               | AFTERTREATMENT COVER Steel, Black                                                                                                                                                                                                                                                       |
| 7BLW               | EXHAUST SYSTEM Horizontal Aftertreatment System, Frame Mounted Right Side Under Cab, for Single Vertical Tail Pipe, Frame Mounted Right Side Back of Cab                                                                                                                                |
| 7WAZ               | TAIL PIPE (1) Turnback Type                                                                                                                                                                                                                                                             |
| 7WDM               | EXHAUST HEIGHT 10'                                                                                                                                                                                                                                                                      |
| 7WDN               | MUFFLER/TAIL PIPE GUARD (1) Aluminum                                                                                                                                                                                                                                                    |
| 8000               | ELECTRICAL SYSTEM 12-Volt, Standard Equipment                                                                                                                                                                                                                                           |
|                    | <b><u>Includes</u></b>                                                                                                                                                                                                                                                                  |
|                    | : DATA LINK CONNECTOR For Vehicle Programming and Diagnostics In Cab                                                                                                                                                                                                                    |
|                    | : HAZARD SWITCH Push On/Push Off, Located on Instrument Panel to Right of Steering Wheel                                                                                                                                                                                                |
|                    | : HEADLIGHT DIMMER SWITCH Integral with Turn Signal Lever                                                                                                                                                                                                                               |
|                    | : PARKING LIGHT Integral with Front Turn Signal and Rear Tail Light                                                                                                                                                                                                                     |
|                    | : STARTER SWITCH Electric, Key Operated                                                                                                                                                                                                                                                 |
|                    | : STOP, TURN, TAIL & B/U LIGHTS Dual, Rear, Combination with Reflector                                                                                                                                                                                                                  |
|                    | : TURN SIGNAL SWITCH Self-Cancelling for Trucks, Manual Cancelling for Tractors, with Lane Change Feature                                                                                                                                                                               |
|                    | : TURN SIGNALS, FRONT Includes Reflectors and Auxiliary Side Turn Signals, Solid State Flashers; Flush Mounted                                                                                                                                                                          |
|                    | : WINDSHIELD WIPER SWITCH 2-Speed with Wash and Intermittent Feature (5 Pre-Set Delays), Integral with Turn Signal Lever                                                                                                                                                                |
|                    | : WINDSHIELD WIPERS Single Motor, Electric, Cowl Mounted                                                                                                                                                                                                                                |
|                    | : WIRING, CHASSIS Color Coded and Continuously Numbered                                                                                                                                                                                                                                 |
| 8518               | CIGAR LIGHTER Includes Ash Cup                                                                                                                                                                                                                                                          |
| 8GXD               | ALTERNATOR {Leece-Neville AVI160P2013} Brush Type, 12 Volt, 160 Amp Capacity, Pad Mount, with Remote Sense                                                                                                                                                                              |
| 8HAE               | BODY BUILDER WIRING Rear of Frame; Includes Sealed Connectors for Tail/Amber Turn/Marker/ Backup/ Accessory Power/Ground and Sealed Connector for Stop/Turn                                                                                                                             |
| 8HAH               | ELECTRIC TRAILER BRAKE/LIGHTS Accommodation Package to Rear of Frame; for Combined Trailer Stop, Tail, Turn, Marker Light Circuits; Includes Electric Trailer Brake Accommodation Package with Cab Connections for Mounting Customer Installed Electric Brake Unit, Less Trailer Socket |
| 8MJT               | BATTERY SYSTEM {Fleetrite} Maintenance-Free, (2) 12-Volt 1900CCA Total, Top Threaded Stud                                                                                                                                                                                               |
| 8RGA               | 2-WAY RADIO Wiring Effects; Wiring with 20 Amp Fuse Protection, Includes Ignition Wire with 5 Amp Fuse, Wire Ends Heat Shrink and Routed to Center of Header Console in Cab                                                                                                             |

| <b><u>Code</u></b> | <b><u>Description</u></b>                                                                                                                                                                                                                                                                                                           |
|--------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 8RMZ               | SPEAKERS (2) 6.5" Dual Cone Mounted in Both Doors, (2) 5.25" Dual Cone Mounted in Both B-Pillars                                                                                                                                                                                                                                    |
| 8RPP               | ANTENNA Shark Fin, Roof Mounted                                                                                                                                                                                                                                                                                                     |
| 8RPS               | RADIO AM/FM/WB/Clock/Bluetooth/USB Input/Auxiliary Input                                                                                                                                                                                                                                                                            |
| 8RRK               | CAMERA SYSTEM Prewire, Four Camera Input Capable, Camera One Input Pre-configured for Reverse, Blunt Cut Circuits for Three Camera Inputs, Includes One Camera in Bag Shipped Loose in Cab, Display Mounted to Dash, 5' Cable Coiled at End of Frame                                                                                |
| 8TKK               | TRAILER AUXILIARY FEED CIRCUIT for Electric Trailer Brake Accommodation/Air Trailer ABS; with 30 Amp Fuse and Relay, Controlled by Ignition Switch                                                                                                                                                                                  |
| 8TPR               | STOP, TURN, TAIL & B/U LIGHTS {Weldon} Multi-Function LED Lamp, Mounted Outside Rails, Includes LED License Plate Light                                                                                                                                                                                                             |
| 8VBE               | HORN, ELECTRIC (1) Trumpet Style                                                                                                                                                                                                                                                                                                    |
| 8VZK               | TURN SIGNALS, FRONT Dual Face, LED, Amber/Red, Mounted on Top of Fender, Used with Standard Flush Mounted Front Turn Signal, Side Marker Lamps, Parking Lights and Reflectors                                                                                                                                                       |
| 8WPH               | CLEARANCE/MARKER LIGHTS (5) {Truck Lite} Amber LED Lights, Flush Mounted on Cab or Sunshade                                                                                                                                                                                                                                         |
| 8WPZ               | TEST EXTERIOR LIGHTS Pre-Trip Inspection will Cycle all Exterior Lamps Except Back-up Lights                                                                                                                                                                                                                                        |
| 8WTK               | STARTING MOTOR {Delco Remy 38MT Type 300} 12 Volt, Less Thermal Over-Crank Protection                                                                                                                                                                                                                                               |
| 8WWJ               | INDICATOR, LOW COOLANT LEVEL with Audible Alarm                                                                                                                                                                                                                                                                                     |
| 8XAH               | CIRCUIT BREAKERS Manual-Reset (Main Panel) SAE Type III with Trip Indicators, Replaces All Fuses                                                                                                                                                                                                                                    |
| 8XDU               | BATTERY BOX Steel, with Aluminum Cover, 14" Wide, 2-3 Battery Capacity, Mounted Left Side Under Cab                                                                                                                                                                                                                                 |
| 8XHN               | HORN, AIR Single Trumpet, Black, with Lanyard Pull Cord                                                                                                                                                                                                                                                                             |
| 8XNY               | HEADLIGHTS Halogen                                                                                                                                                                                                                                                                                                                  |
| 8XPN               | USB PORT One USB-A Port and One USB-C Port, Located in Instrument Panel                                                                                                                                                                                                                                                             |
| 9AAB               | LOGOS EXTERIOR Model Badges                                                                                                                                                                                                                                                                                                         |
| 9AAE               | LOGOS EXTERIOR, ENGINE Badges                                                                                                                                                                                                                                                                                                       |
| 9HCW               | GRILLE Molded in Black                                                                                                                                                                                                                                                                                                              |
| 9WBN               | FENDER EXTENSIONS Painted                                                                                                                                                                                                                                                                                                           |
| 9WBW               | FRONT END Tilting, Fiberglass, with Three Piece Construction, Dual Air Intakes                                                                                                                                                                                                                                                      |
| 10060              | PAINT SCHEMATIC, PT-1 Single Color, Design 100                                                                                                                                                                                                                                                                                      |
|                    | <b><u>Includes</u></b><br>: PAINT SCHEMATIC ID LETTERS "WP"                                                                                                                                                                                                                                                                         |
| 10761              | PAINT TYPE Base Coat/Clear Coat, 1-2 Tone                                                                                                                                                                                                                                                                                           |
| 10AGB              | COMMUNICATIONS MODULE Telematics Device with Over the Air Programming; Includes Five Year Data Plan and International 360                                                                                                                                                                                                           |
| 10UAV              | VEHICLE REGISTRATION IDENTITY ID for Non-CARB Omnibus and/or Non-ACT Adopting State or Exempt Vehicle. Not for use on vehicles registering in CA/MA /OR/NJ/NY/WA. Contains non-mitigated legacy engine & cannot be registered in CA unless exempt. You may be held liable under state law for failure to properly register vehicle. |
|                    | <b><u>Notes</u></b><br>: CANNOT BE REGISTERED IN CA. For vehicles that will be registered in States other than CA.                                                                                                                                                                                                                  |
| 10WCY              | SAFETY TRIANGLES                                                                                                                                                                                                                                                                                                                    |

| <b><u>Code</u></b> | <b><u>Description</u></b>                                                                                                                                                                      |
|--------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 10WUE              | MUD FLAPS, FRONT WHEELS (2) Rubber, Mounted on Fender Extension                                                                                                                                |
| 10XAN              | FIRE EXTINGUISHER 5 lb Class A B C                                                                                                                                                             |
| 10XAP              | FIRE EXTINGUISHER BRACKET Mounted Left Side Driver Seat                                                                                                                                        |
| 11001              | CLUTCH Omit Item (Clutch & Control)                                                                                                                                                            |
| 12703              | ANTI-FREEZE Red, Extended Life Coolant; To -40 Degrees F/ -40 Degrees C, Freeze Protection                                                                                                     |
| 12849              | BLOCK HEATER, ENGINE 120V/1000W, for Cummins ISB/B6.7/ISL/L9 Engines                                                                                                                           |
|                    | <u>Includes</u><br>: BLOCK HEATER SOCKET Receptacle Type; Mounted below Drivers Door                                                                                                           |
| 12EXU              | ENGINE, DIESEL {Cummins B6.7 250} EPA 2024, 250HP @ 2400 RPM, 660 lb-ft Torque @ 1600 RPM, 2600 RPM Governed Speed, 250 Peak HP (Max)                                                          |
| 12THT              | FAN DRIVE {Horton Drivemaster} Two-Speed Type, Direct Drive, with Residual Torque Device for Disengaged Fan Speed                                                                              |
|                    | <u>Includes</u><br>: FAN Nylon                                                                                                                                                                 |
| 12VCE              | AIR CLEANER Single Element, Fire Retardant Media                                                                                                                                               |
| 12VKB              | EMISSION, CALENDAR YEAR {Cummins B6.7} EPA, OBD and GHG Certified for Calendar Year 2025                                                                                                       |
| 12VXV              | THROTTLE, HAND CONTROL Engine Speed Control for PTO; Electronic, Mobile, Variable Speed; (Range 2 to 20 MPH) Mounted on Steering Wheel                                                         |
| 12WPV              | OIL PAN 15 Quart Capacity, For Cummins ISB/B6.7 Engines                                                                                                                                        |
| 12WVG              | EPA IDLE COMPLIANCE Low NOx Idle Engine, Complies with EPA Clean Air Regulations; Includes "Certified Clean Idle" Decal on Hood                                                                |
| 12WZE              | CARB IDLE COMPLIANCE Does Not Comply with California Clean Air Idle Regulations                                                                                                                |
| 12XBM              | ENGINE CONTROL, REMOTE MOUNTED Provision for; Includes Wiring for Body Builder Installation of PTO Controls and Starter Lockout, with Ignition Switch Control, for Cummins B6.7 and L9 Engines |
| 12XCC              | RADIATOR Aluminum, 2-Row, Down Flow, Front to Back System, 640 SqIn Louvered, with 383 SqIn Charge Air Cooler, Includes In-Tank Oil Cooler                                                     |
| 12XCS              | CARB EMISSION WARR COMPLIANCE Does Not Comply with CARB Emission Warranty                                                                                                                      |
| 13BBK              | TRANSMISSION, AUTOMATIC {Allison 2500 RDS} 6th Generation Controls, Wide Ratio, 6-Speed with Double Overdrive, with PTO Provision, Less Retarder, with 33,000-lb GVW and GCW Max               |
| 13WDH              | WIRING, TRANSMISSION Installed Wiring for Transmission/PTO Controls, for Allison 1000, 2000, 2100, 2200, 2400, 2500 Series Transmission                                                        |
| 13WEX              | TRANSMISSION SHIFT CONTROL Column Mounted Stalk Shifter, for Allison 1000 & 2000 Series Transmission                                                                                           |
| 13WLN              | TRANSMISSION OIL Synthetic; 20 thru 28 Pints                                                                                                                                                   |
| 13WUA              | AUTOMATIC NEUTRAL Allison Transmission Shifts to Neutral When Parking Brake is Engaged and Remains in Neutral When Parking Brake is Disengaged, with On/Off Switch                             |
| 13WVV              | NEUTRAL AT STOP Allison Transmission Shifts to Neutral When Service Brake is Depressed and Vehicle is at Stop; Remains in Neutral Until Service Brake is Released                              |
| 13WYY              | SHIFT CONTROL PARAMETERS {Allison} 1000 or 2000 Series Transmissions, Performance Programming                                                                                                  |
| 13XAA              | PTO CONTROL, DASH MOUNTED For Customer Provided PTO; Includes Switch, Electric/Air Solenoid, Piping and Wiring                                                                                 |



| <b><u>Code</u></b> | <b><u>Description</u></b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
|--------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 13XAC              | ALLISON SPARE INPUT/OUTPUT for Rugged Duty Series (RDS), General Purpose Trucks, Package Number 354, Modified for Single Input Auto Neutral                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| 13XAK              | PTO LOCATION Customer Intends to Install PTO at Right Side of Transmission                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| 14ANR              | AXLE, REAR, SINGLE {Meritor MS-17-14X-3DCL} Single Reduction, 17,500-lb Capacity, Driver Controlled Locking Differential, 190 Wheel Ends . Gear Ratio: 5.57                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| 14VAH              | SUSPENSION, REAR, SINGLE 23,500-lb Capacity, Vari-Rate Springs, with 4500-lb Capacity Auxiliary Rubber Springs                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| 15LMR              | FUEL/WATER SEPARATOR {Racor 400 Series,} with Primer Pump, Includes Water-in-Fuel Sensor                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| 15LRE              | LOCATION FUEL/WATER SEPARATOR Mounted Under Hood, Left Side, Above Front Axle                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| 15SXJ              | FUEL TANK Top Draw, Non-Polished Aluminum, 24" Dia, 50 US Gal (189L), Mounted Left Side, Under Cab                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| 15WCN              | DEF TANK 5 US Gal (19L) Capacity, Frame Mounted Outside Left Rail, Under Cab                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| 16030              | CAB Conventional, Day Cab                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
|                    | <u>Includes</u><br>: CLEARANCE/MARKER LIGHTS (5) Flush Mounted                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| 16BAM              | AIR CONDITIONER with Integral Heater and Defroster                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| 16GED              | GAUGE CLUSTER Base Level; English with English Electronic Speedometer                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|                    | <u>Includes</u><br>: GAUGE CLUSTER DISPLAY: Base Level (3" Monochromatic Display), Premium Level (5" LCD Color Display); Odometer, Voltmeter, Diagnostic Messages, Gear Indicator, Trip Odometer, Total Engine Hours, Trip Hours, MPG, Distance to Empty/Refill for<br>: GAUGE CLUSTER Speedometer, Tachometer, Engine Coolant Temp, Fuel Gauge, DEF Gauge, Oil Pressure Gauge, Primary and Secondary Air Pressure or Auxiliary Air Pressure (if Air Equipped)<br>: WARNING SYSTEM Low Fuel, Low DEF, Low Oil Pressure, High Engine Coolant Temp, Low Battery Voltage (Visual and Audible), Low Air Pressure, Primary and Secondary (if Air Equipped) |
| 16GHU              | GRAB HANDLE, CAB INTERIOR (2) Safety Yellow                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| 16HGH              | GAUGE, OIL TEMP, AUTO TRANS for Allison Transmission                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| 16HHE              | GAUGE, AIR CLEANER RESTRICTION {Filter-Minder} Mounted in Instrument Panel                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| 16HKT              | IP CLUSTER DISPLAY On Board Diagnostics Display of Fault Codes in Gauge Cluster                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| 16KCA              | SEAT, DRIVER {National 2000 195} Air Suspension, High Back with Integral Headrest, Vinyl, Isolator, 8" Adjuster, 1 Chamber Lumbar, 2 Position Front Cushion Adjust, 6-23 Degree Seat Back Angle Adjust, Dual Shocks                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| 16SMP              | SEAT, TWO-MAN PASSENGER {National} Vinyl, Less Under Seat Storage Compartment                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| 16SNS              | MIRRORS (2) Aero Pedestal, Power Adjust, Heated, Black Heads and Arms, 6.5" x 14" Flat Glass, Includes 6.5" x 6" Convex Mirrors, for 102" Load Width                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|                    | <u>Notes</u><br>: Mirror Dimensions are Rounded to the Nearest 0.5"                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| 16SNW              | MIRROR, CONVEX, LOOK DOWN Right Side, Black, 6" x 10.5"                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| 16VKB              | CAB INTERIOR TRIM Classic, for Day Cab                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
|                    | <u>Includes</u><br>: CONSOLE, OVERHEAD Molded Plastic with Dual Storage Pockets, Retainer Nets and CB Radio Pocket; Located Above Driver and Passenger<br>: DOME LIGHT, CAB Door Activated and Push On-Off at Light Lens, Timed Theater Dimming, Integral to Overhead Console, Center Mounted                                                                                                                                                                                                                                                                                                                                                         |

| <b><u>Code</u></b> | <b><u>Description</u></b>                                                                                                                                                                                 |
|--------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                    | : SUN VISOR (2) Padded Vinyl; 2 Moveable (Front-to-Side) Primary Visors, Driver Side with Toll Ticket Strap                                                                                               |
| 16VLK              | CAB REAR SUSPENSION Air Suspension, for Mid Cab Height                                                                                                                                                    |
| 16WBY              | ARM REST, RIGHT, DRIVER SEAT                                                                                                                                                                              |
| 16WHJ              | HOSE CLAMPS, HEATER HOSE {Breeze} Belleville Washer Type                                                                                                                                                  |
| 16WJU              | WINDOW, POWER (2) and Power Door Locks, Left and Right Doors, Includes Express Down Feature                                                                                                               |
| 16WLS              | FRESH AIR FILTER Attached to Air Intake Cover on Cowl Tray in Front of Windshield Under Hood                                                                                                              |
| 16WSE              | LOW WASHER FLUID INDICATOR                                                                                                                                                                                |
| 16XDS              | TELEMATICS BRACKET with Universal Mount, 1" Ball Mount Size, for Customer Supplied Telematics Device, Mounted in Auxiliary Gauge Location in Flat Panel, Includes (1) APO, (1) USB-A Port, (1) USB-C Port |
| 16XJN              | INSTRUMENT PANEL Flat Panel                                                                                                                                                                               |
| 16XWD              | SUNSHADE, EXTERIOR Aerodynamic, Painted Roof Color, with Integral Clearance/Marker Lights                                                                                                                 |
| 16ZBT              | ACCESS, CAB Steel, Driver & Passenger Sides, Two Steps per Door, for use with Day Cab and Extended Cab                                                                                                    |
| 27DJM              | WHEELS, FRONT {Maxion 91541} DISC; 22.5x8.25 Rims, Painted Steel, 2-Hand Hole, 10-Stud, 285.75mm BC, Hub-Piloted, Flanged Nut, with Steel Hubs                                                            |
| 28DJM              | WHEELS, REAR {Maxion 91541} DUAL DISC; 22.5x8.25 Rims, Painted Steel, 2-Hand Hole, 10-Stud, 285.75mm BC, Hub-Piloted, Flanged Nut, with Steel Hubs                                                        |
| 29PAR              | PAINT IDENTITY, FRONT WHEELS Disc Front Wheels; with Vendor Applied White Powder Coat Paint                                                                                                               |
| 29PAS              | PAINT IDENTITY, REAR WHEELS Disc Rear Wheels; with Vendor Applied White Powder Coat Paint                                                                                                                 |
| 29WLK              | WHEEL BEARING, FRONT, LUBE {EmGard FE-75W-90} Synthetic Oil                                                                                                                                               |
| 7372135809         | (4) TIRE, REAR 11R22.5 Load Range G AH37 (HANKOOK), 501 rev/mile, 75 MPH, All-Position                                                                                                                    |
| 7382135809         | (2) TIRE, FRONT 11R22.5 Load Range H AH37 (HANKOOK), 499 rev/mile, 75 MPH, All-Position                                                                                                                   |

**Services Section:**

|       |                                                                                                                                                                                                                                                                                   |
|-------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 40129 | WARRANTY Standard for MV Series, Effective with Vehicles Built July 1, 2017 or Later, CTS-2020A                                                                                                                                                                                   |
| 40RBG | SERVICES, TOWING Service Call to 24-Month/Unlimited Mileage to the Nearest Navistar Dealer for Navistar Warrantable Failure as Contract Defined; Includes Engine Failure if Supplier Declines Tow Coverage & ESC Supplied thru Navistar; \$550 (USA) Maximum Benefit per Incident |
| 40TUU | SRV CONTRACT, EXT ALLISON XMSN To 60-Month/Unlimited Miles/km, for Allison 2500 RDS with P&D or Beverage Vocations (ST09-ST13)                                                                                                                                                    |
| 40YYK | SRV CONT, EXT CUMMINS ENG/AFTR To 60-Month/150,000 Miles (240,000 km), Extended Cummins B6.7 Engine Coverage, Protection Plan 1 and Aftertreatment, (Truck Application Only)                                                                                                      |

1 10 ft box dump

tariff

| <u>Description</u>                          | (US DOLLAR) | <u>Price</u>  |
|---------------------------------------------|-------------|---------------|
| Total Factory List Price Including Options: |             | \$141,638.00  |
| Total Goods Purchased:                      |             | \$2,000.00    |
| Lot charge                                  |             |               |
| Freight fuel                                |             |               |
| Total Preparation And Delivery:             |             | \$1,000.00    |
| Freight                                     |             |               |
| Total Freight:                              |             | \$3,100.00    |
| Total Factory List Price Including Freight: |             | \$147,738.00  |
| Less Customer Allowance:                    |             | (\$51,352.57) |
| Total Vehicle Price:                        |             | \$96,385.43   |
| Total Body/Allied Equipment:                |             | \$28,435.00   |
| Total Sale Price:                           |             | \$124,820.43  |
| Total Per Vehicle Sales Price:              |             | \$124,820.43  |
| Total Net Sales Excluding Taxes:            |             | \$124,820.43  |
| IMF                                         |             |               |
| Total License, Title:                       |             | \$500.00      |
| Net Sales Price:                            |             | \$125,320.43  |

Please feel free to contact me regarding these specifications should your interests or needs change. I am confident you will be pleased with the quality and service of an International vehicle.

Approved by Seller:

Accepted by Purchaser:

\_\_\_\_\_  
Official Title and Date

\_\_\_\_\_  
Firm or Business Name

\_\_\_\_\_  
Authorized Signature

\_\_\_\_\_  
Authorized Signature and Date

This proposal is not binding upon the seller without  
Seller's Authorized Signature

\_\_\_\_\_  
Official Title and Date

The TOPS FET calculation is an estimate for reference purposes only. The seller or retailer is responsible for calculating and reporting/paying appropriate FET to the IRS.

The limited warranties applicable to the vehicles described herein are Navistar, Inc.'s standard printed warranties which are incorporated herein by reference and to which you have been provided a copy and hereby agree to their terms and conditions.

